

5

**APPLICATION FOR UNITED STATES LETTER PATENT**  
**FOR**  
**METHOD AND APPARATUS TO IMPROVE FILE MANAGEMENT**

**Inventor(s): Steven Dake**

**Prepared By: John F. Kacvinsky**  
**Senior Patent Attorney**

**Intel Corporation**  
3500 Brooktree Road, Suite 100  
Wexford, PA 15090  
Phone: (724) 933-3377  
Facsimile: (724) 933-3350

30 "Express Mail" label number EL034437149US

FIELD

## BACKGROUND

There are disadvantages, however, associated with this type of system design. One disadvantage is that a component may have to remain idle as it waits for information from another component. Idle time may represent an inefficient use of system resources.

5

**0363-9780**

10    Embodiments of the invention, however, both as to organization and method of  
operation, together with objects, features, and advantages thereof, may best be  
understood by reference to the following detailed description when read with the  
accompanying drawings in which:

FIG. 2 is a block diagram of a client system in accordance with one embodiment of the invention.

FIG. 4 is a block flow diagram of operations performed by a client system in accordance with one embodiment of the invention.

12/29/00

DETAILED DESCRIPTION

In the following detailed description, numerous specific details are set forth in order to provide a thorough understanding of the embodiments of the invention. It will be understood by those skilled in the art, however, that the embodiments of the invention may be practiced without these specific details. In other instances, well-known methods, procedures, components and circuits have not been described in detail so as not to obscure the embodiments of the invention.

Embodiments of the invention may improve performance of a distributed system by reducing idle time for distributed components as well as bandwidth demands for the interconnect system. More particularly, one embodiment of the invention may improve performance of a distributed system used for file management. Consequently, this may reduce delays associated with file operations. Accordingly, a user may benefit in terms of more responsive applications and services.

A file management system typically comprises a client and a server. A client in this context may refer to a requestor of services. A server in this context may refer to a provider of services. The client typically sends a file request to a server over an interconnect system. The file request may be in the form of a message, and may include a function request and a file name. A message in this context may comprise one or more alphanumeric characters, symbols or logical expressions that when combined represent, for example, control words, commands, instructions, information or data. The message could vary in composition from a single bit to entire phrases, for example. The server associates a unique identifier with the file name, identifies location information for the file, and stores it with the unique identifier. The server then sends the unique identifier

[illegible]

5

15

20

0210210

With respect to the second disadvantage, the client and server may need to communicate unnecessary information to perform the assignment function, thereby increasing demands on the interconnect system. A file management system as described above requires at least two messages. The client sends a first message to the server requesting assignment of a unique identifier to a file name. The server sends a second message to the client with the unique identifier. Each message requires use of a certain amount of bandwidth from the interconnect system. Bandwidth in this context may refer to the speed at which information can be transferred over an interconnect system, and is typically measured in kilobits per second (kbps). By way of contrast, one embodiment of the invention may perform the assignment process using only one message, thereby potentially reducing bandwidth demands on the interconnect system by as much as 50%.

Embodiments of the invention may improve performance of a distributed system by reducing idle time for a client as well as bandwidth demands for the interconnect system. One embodiment of the invention assigns a unique identifier to a file name at the client, and sends the unique identifier to the server. This may reduce client idle time since the client may begin processing subsequent file requests without having to wait for a message from the server. This may also reduce bandwidth demands since the server does not need to send a message back to the server to complete the assignment process,

[illegible]

characteristic described in connection with the embodiment may be included in at least one embodiment of the invention. The appearances of the phrase “in one embodiment” in various places in the specification do not necessarily all refer to the same embodiment.

10 practicing one embodiment of the invention. As shown in FIG. 1, system 100 comprises a client 102 and a server 106 connected by an interconnect system 104. The term “client” as used herein may refer to any requestor of information. The term “server” as used herein may refer to any provider of information.

of the invention. FIG. 2 illustrates a client 200 that may be representative of client 102. As shown in FIG. 2, client 200 comprises a processor 202, a memory 204 and an interface 208, all connected by connection 210. Memory 204 may store program instructions and data. The term “program instructions” include computer code segments comprising words, values and symbols from a predefined computer language that, when placed in combination according to a predefined manner or syntax, cause a processor to perform a certain function. Examples of a computer language include C, C++ and assembly. Processor 202 executes the program instructions, and processes the data, stored in memory 204. Interface 208 coordinates the transport of data from client 200 to

**00000000000000000000**

5

10

15

20



5 File system interface 206 may be an interface that operates to provide access to one or more files for system 100. An interface in this context may refer to a defined protocol by which one software module may access functionality from another software module. A file in this context refers to a discrete set of data stored in memory, such as in memory 204 or a hard drive. File system interface 206 may receive a request to perform 10 certain operations for a file, such as create, open, seek, read, write, rename, delete, copy, move, and so forth. The request may originate from a host OS or an application program, for example. A host OS may comprise an OS for a system. For example, if an embodiment of the invention was implemented as part of a personal computer, the host OS might comprise an OS sold by Microsoft Corporation, such as Microsoft Windows® 15 95, 98, 2000 and NT, for example.

In one embodiment of the invention file system interface 206 operates as an Operating System Service Module (OSM) as defined by the Intelligent I/O Specification (I<sub>2</sub>O) developed by the I<sub>2</sub>O Special Interest Group (SIG) (I<sub>2</sub>O SIG), version 1.5, adopted in April of 1997, and available from “[www.i20sig.org](http://www.i20sig.org)” (“I<sub>2</sub>O Specification”), although the invention is not limited in scope in this respect.

12/29/00

This may improve I/O performance as well as permit the CPU or other processor to provide processing functionality for other tasks. An interrupt in this context refers to a request to access an I/O device, such as a hard drive, floppy disk drive, printer, monitor, keyboard, network interface card (NIC) and so forth.

The I<sub>2</sub>O Specification defines a communications model that comprises a message-passing system. The OSM, ISM and HDM communicate and coordinate operations by passing information in the form of messages through a message layer. A message layer in this context may manage and dispatch requests, provide a set of Application Programming Interfaces (APIs) for delivering messages, and provide a set of support routines to process messages.

12/29/00

system interface 206 receives file requests from an application program via the host OS, translates the request into a message in accordance with the I<sub>2</sub>O Specification, and sends it to a file system manager (described below) for processing. An application program in this context refers to a program that provides a predetermined set of functions for specialized tasks, typically having a user interface to facilitate the processing of commands and instructions between a user and the computer system. Examples of application programs might include a word processor, spread sheet, database or Internet browser.

Interface 208 may comprise any suitable technique for controlling communication signals between computer or network devices using a desired set of communications protocols, services and operating procedures, for example. In one embodiment of the invention, interface 208 may operate, for example, in accordance with the PCI Specification and the I<sub>2</sub>O Specification. In another embodiment of the invention, interface 208 may operate in accordance with the Transmission Control Protocol (TCP) as defined by the Internet Engineering Task Force (IETF) standard 7, Request For Comment (RFC) 793, adopted in September, 1981, and the Internet Protocol (IP) as defined by the IETF standard 5, RFC 791, adopted in September, 1981, both available from "[www.ietf.org](http://www.ietf.org)." Although interface 208 may operate with in accordance with the above described protocols, it can be appreciated that interface 208 may operate with any suitable technique for controlling communication signals between computer or network devices using a desired set of communications protocols, services and operating procedures, for example, and still fall within the scope of the invention.

Interface 208 also includes connectors for connecting interface 208 with a suitable communications medium. Interface 208 may receive communication signals over any suitable medium such as copper leads, twisted-pair wire, co-axial cable, fiber optics, radio frequencies, and so forth. In one embodiment of the invention, the connectors are suitable for use with a bus to carry signals that comply with the PCI Specification.

FIG. 3 is a block diagram of a server system in accordance with one embodiment of the invention. FIG. 3 illustrates a server 300 that is representative of server 106, in accordance with one embodiment of the invention. As shown in FIG. 3, server 300 comprises a processor 302, a memory 304 and an interface 308, all connected by connection 310. Elements 302, 304, 308 and 310 of FIG. 3 are similar in structure and operation as corresponding elements 202, 204, 208 and 210 described with reference to FIG. 2. Although server 300 is shown with a processor 302, it can be appreciated that server 300 may operate without processor 302 by using another processor available to server 300 (e.g., processor 202), and still fall within the scope of the invention. For example, such a configuration may occur if the embodiments of the invention were incorporated into a personal computer where the client and server were connected by a PCI bus and both shared a single processor.

In one embodiment of the invention, memory 304 contains program instructions for a file system manager 306. File system manager 306 performs file management and provides access to a storage medium (not shown) containing a plurality of files. File system 306 performs file operations such as create, open, seek, read, write, rename, delete, copy, move, and so forth, in response to file requests received from file system interface 206. One example of file system interface 206 includes an ISM operating in

accordance with the I<sub>2</sub>O Specification, although the scope of the invention is not limited in this respect.

The operation of systems 100, 200 and 300 will be described in more detail with reference to FIGS. 4 and 5. Although FIGS. 4 and 5 presented herein include a particular sequence of operations, it can be appreciated that the sequence of operations merely provides an example of how the general functionality described herein may be implemented. Further, the sequence of operations does not necessarily have to be executed in the order presented unless otherwise indicated.

FIG. 4 is a block flow diagram of the operations performed by a client in accordance with one embodiment of the invention. In this embodiment of the invention, file system interface 206 operates as part of client 106. It can be appreciated that file system interface 206, however, can be implemented by any device, or combination of devices, located anywhere in a computer or network system and still fall within the scope of the invention.

As shown in FIG. 4, a client receives a request to access a file having a file name at block 402. The client associates the file name with an identifier at block 404. The client sends the associated identifier and file name to a server at block 406. The client stores the associated identifier and file name in memory at block 408. The client receives an acknowledgement message from the server at block 410.

Once the client assigns an identifier to a file, the identifier is used for future requests for the file. The client receives a second request at the client to access the file. The client retrieves the identifier associated with the file name from memory. The client sends the second request to the server using the associated identifier.

FIG. 5 is a block flow diagram of the operations performed by a server in accordance with one embodiment of the invention. In this embodiment of the invention, file system manager 306 operates as part of client 106. It can be appreciated that this functionality, however, can be implemented by any device, or combination of devices, located anywhere in a computer or network system and still fall within the scope of the invention.

As shown in FIG. 5, a server receives a file name and associated identifier for a file at block 502. The server sends an acknowledgement message to the client at block 504. The server searches for location information for the file at block 506. The server associates the location information with the identifier at block 508. The server stores the associated location information and identifier in memory.

Once the server indexes the location information for a file using the identifier, the server can use the identifier to access the location information for subsequent file requests. The server receives a second request to access the file having the identifier. The server retrieves the location information from memory using the identifier.

The operation of systems 100, 200 and 300, and the flow diagrams shown in FIGS. 4 and 5, may be better understood by way of example. An application program sends a request to read information from a file with a file name "test file one" to the host OS of system 100. A unique identifier in this context refers to a series of alphanumeric characters that when combined represent a unique word, value or binary string to the client, server and/or system with respect to other words, values or binary strings used by the client, server and/or system. The host OS passes the file request to file system interface 206. File system interface 206 generates a unique identifier "A123" and assigns

5

10

15

20

**SECRET**

5

10

20



097168P-1200

5

10

20

may use the stream forest ISM to manage groupings of file systems within an IRTOS environment. The stream tree OSM may use the stream tree ISM to manage a file system within an I<sub>2</sub>O Real-Time Operating System (RTOS) environment. The stream forest OSM and stream tree OSM may communicate with the stream forest OSM and stream tree ISM, respectively, using the stream messaging scheme. This embodiment of the invention will be further described with reference to FIG. 7.

FIG. 6 illustrates a software architecture in accordance with one embodiment of the invention. As shown in FIG. 6, a system 600 may comprise a file system interface having a stream forest OSM 602, a Linux OS 604, a Linux Virtual File System (VFS) 606, a stream tree OSM 608, and one or more Linux I<sub>2</sub>O drivers 610. Linux I<sub>2</sub>O drivers 610 may operate in accordance with the Linux Kernel and the I<sub>2</sub>O Specification. Linux I<sub>2</sub>O drivers 610 may include PCI I<sub>2</sub>O drivers 612. PCI I<sub>2</sub>O drivers 612 may operate in accordance with the PCI Specification and the I<sub>2</sub>O Specification.

The file system interface communicates with a file system manager over a bus 614 that communicates signals in accordance with the PCI Specification. The file system manager may comprise a stream forest ISM 616, a stream tree ISM 618, a Redundant Array of Inexpensive Disks (RAID) ISM 620, a Small Computer System Interface (SCSI) HDM 622 and IRTOS 624.

In this embodiment of the invention, the modules shown in system 600 may be implemented using the C programming language, although the scope of the invention is not limited in this respect. Further, in this embodiment of the invention modules shown in system 600 support identifiers having a length of 255 characters.

5 Stream tree OSM 608 may be configured to operate with Linux OS 604 using, for example, the Linux Kernel. Stream tree OSM 608 may support a stream tree ISM, such as stream tree ISM 618.

Stream forest OSM 602 may function to create a stream tree within a stream forest, using a function name such as “IOCTL\_SF\_TREECREATE.” This function may accept as inputs, for example, an input buffer defined in the C language as follows:

15

Stream forest OSM 602 may also function to rename an existing stream tree, using a function name such as “IOCTL\_SF\_TREERENAME.” This function may accept as inputs, for example, an input buffer defined in the C language as follows:

25

**09-06-2017**

```

5 struct ik_sf_treeerase {
        char IdentifierToErase[256];
    }.

```

10 Stream forest OSM 602 may use one or more of the following data structures. A data structure referred to herein as a “super block” may be used to represent the initial “inode” of a file system. An “inode” in this context may refer to a file node of the file system. A super block operation list may be a grouping of functions used to manipulate the super block. An inode record data structure may be used to represent each file node of the file system. An inode operation list may be a grouping of functions used to manipulate an inode. A file record data structure may be used to represent an abstract file within a file system. A file operation list may be used to support file operations. All of these data structures combined with operation list operations may be used to represent a file system.

Stream tree class messages may be issued for several of the data structures. A  
20 stream tree class message may be issued, for example, for the inode operations create,  
lookup, make directory (“mkdir”), remove directory (“rmdir”), and rename directory. A  
stream tree class message may be issued for various file operations, such as open, read,  
write, seek, and close.

Stream forest OSM 602 may register the contained file system with the identifier “i2ofs,” for example, within the Linux kernel. Stream forest OSM 602 may use the NULL identifier for the root tree cone container, for example. Stream forest OSM 602

may use the identifier '.' for the current tree cone container, for example. Stream forest OSM 602 may use the identifier '..' for the parent tree cone container, for example.

System 600 may contain system descriptions for one or more of the following modules:

1. A MODULE\_AUTHOR description for the kernel;
2. A MODULE\_DESCRIPTION of "I2O Filesystem Offload Driver";
3. A module\_init () which may register the file system;
4. A module\_exit () which may un-register the file system;
5. A DECLARE\_FSTYPE module which may have parameters of the i2ofs\_type i2ofs, read super operation, and 0;
6. An OSM handle manager module that may have a first handle of zero that increases by 1 per used handle;
  - a. An internal software interface AcquireHandle() which may retrieve an unused handle; and
  - b. An internal software interface ReleaseHandle (int) which may release a currently used handle into the free pool.

System 600 may also provide the function **VFS i2ofs\_read\_super (struct super\_block \*sb, void \*options, int silent)**. This function may accept the inputs as defined in Table 1.

TABLE 1

Variable Type	Variable Identifier	Description
Struct super_block *	Sb	This input may specify the location where the super block should be set.
Void *	Options	This input may specify the options passed by mount.
int	Silent	This input may specify if the mount operation is silent.



```

    struct super_operations *s_op;
    struct dquot_operations *dq_op;
    unsigned long s_flags;
    unsigned long s_magic;
5    struct dentry *s_root;
    wait_queue_head_t s_wait;
    struct inode *s_ibasket;
    short int s_ibasket_count;
    short int s_ibasket_max;
10   struct list_head s_dirty;
    struct list_head s_files;
    struct block_device *s_bdev;
}.

```

15 The variable super\_block->s\_op may contain the following C functions and provide access to the super block.

```

20 struct super_operations {
    void (*read_inode) (struct inode *);
    void (*write_inode) (struct inode *)
    void (*put_inode) (struct inode *);
    void (*delete_inode) (struct inode *);
    void (*put_super) (struct super_block *);
25 void (*write_super) (struct super_block *);
    void (*statfs) (struct super_block *, struct statfs *);
    int (*remount_fs) (struct super_block *, int *, char *);
    void (*clear_inode) (struct inode);
    void (*umount_begin) (struct super_block *);
30 }.

```

An example of an inode interface may be as follows:

```

35 struct inode {
    struct list_head i_hash;
    struct list_head i_list;
    struct list_head i_dentry;
40 unsigned long i_ino;
    unsigned int i_count;
    kdev_t i_dev;
    umode_t i_mode;
    nlink_t i_nlink;

```

```

uid_t i_uid;
gid_t i_gid;
kdev_t i_rdev;
loff_t I_size;
5  time_t I_atime;
   time_t I_mtime;
   time_t I_ctime;
   unsigned long I_blksize;
   unsigned long I_blocks;
10  unsigned long I_version;
   struct semaphore I_sem;
   struct semaphore I_zombie;
   struct inode_operations *I_op;
   struct file_operations *I_fop;
15  struct super_block *I_sb;
   wait_queue_head_t I_wait;
   struct file_lock *I_flock;
   struct address_space *I_mapping;
   struct address_space I_data;
20  struct dquot *I_dquot[MAXQUOTAS];
   struct pipe_inode_info *I_pipe;
   struct block_device I_bdev;
   unsigned long I_state;
   unsigned int I_flags;
25  unsigned char I_sock;
   atomic_t I_writecount;
   unsigned int I_attr_flags;
   __u32 I_generation;
30  }.

```

The variable inode->i\_op may contain the following C functions and provide method access to the super block, as follows:

```

35  struct inode_operations {
       struct file_operations *default_file_ops;
       int (*create) (struct inode *, const char *, int, int, struct inode **);
       struct dentry * (*lookup) (struct inode *, struct dentry *)
40  int (*link) (struct dentry *, struct inode *, struct dentry *);
       int (*unlink) (struct inode *, struct dentry *);
       int (*symlink) (struct inode *, struct dentry *, const char *);
       int (*mkdir) (struct inode *, struct dentry *, int);
       int (*rmdir) (struct inode *, struct dentry *);

```



5

15

**CONFIDENTIAL**

20

25

- 12/29/00

2. TYPE may be set to 1, indicating a file; and
3. SGL may be set to NewName.

The dereference of NewInode may be set with the new inode structure.

- System 600 may also provide a function **struct dentry \*lookup (struct inode \*,**  
5 **struct dentry \*).** This function may accept the inputs set forth in Table 3.

TABLE 3

Variable Type	Variable Identifier	Description
struct inode *	ParentDirectory	This input may specify the input directory of the lookup operation.

10 This function may send a **StreamConeIdentify** message to stream tree ISM 618. The message may be configured as follows:

1. PARENTHANDLE may be set to the handle identified within the  
15 ParentDirectory inode local data;
2. CHILDHANDLE may be set to a handle retrieved from the OSM handle manager;
3. ATTRIBUTES may be set to STREAMCONECREATE\_QUERY; and
4. SGL may be set to Name.

- 20 The function may create a new inode using **get\_empty\_inode ()**. The function may initialize the new inode by attaching the const char \* variable to it via dentry relationship.

The function may send a **StreamConeGetInformation** message to the stream tree ISM.

The message may be configured as follows:

1. HANDLE may be set to CHILDHANDLE above; and

2. SGL may be set to a local data structure of type Information Result Block.

The function may set the inode values from the Information Result Block. The function may set the dereference of the NewInode variable to the inode that has been created.

System 600 may provide the function **mkdir (struct inode \*, struct dentry \*,**  
 5 **int)**. This function may accept the inputs as set forth in Table 4.

TABLE 4

Variable Type	Variable Identifier	Description
struct inode *	ParentDirectory	This input may specify the input directory of the mkdir operation.
Struct dentry *	Name	This input may specify the name of the object to create.
int	Mode	This input may specify the mode of the new directory.

The function may send a **StreamConeCreate** message to create a directory. The message may be configured as follows:

1. HANDLE may be set to the handle identified in the inode structure input  
 15 ParentDirectory;
2. TYPE may be set to 2; and
3. SGL may be set to the input Name that contains the actual name.

System 600 may provide the function **rmdir (struct inode \*, struct dentry \*)**.

This function may accept the inputs set forth in Table 5.

TABLE 5

Variable Type	Variable Identifier	Description
---------------	---------------------	-------------

struct inode *	ParentDirectory	This input may specify the input directory of the lookup operation.
struct dentry *	Name	This input may specify the name of the object to remove.
int	Length	This input may specify the length of Name in characters.

This function may send a **StreamConeErase** message to remove a directory. The message may be configured as follows:

1. HANDLE may be set to the handle identified in the inode structure input ParentDirectory; and
2. SGL may be set to the input Name.

System 600 may also provide the function **rename (struct inode \*, struct dentry \*, struct inode \*, struct dentry \*)**. This function may accept the inputs set forth in

Table 6.

TABLE 6

Variable Type	Variable Identifier	Description
struct inode *	OldDir	This input may specify the directory of the file to rename.
struct dentry *	OldName	This input may specify the name of the object to rename.
struct inode *	NewDir	This input may specify the new directory of the object.
struct dentry *	NewName	This input may specify the new name of the object.

This function may send a **StreamConeIdentify** message to the ISM. The message may be configured as follows:

1. PARENTHANDLE may be set from OldDir inode internal storage for OSM handles;

- BOOK REVIEW**

System 600 may also provide the function **truncate (struct inode \*)**. This function may accept the inputs set forth in Table 7.

20

25

12/29/00

1. HANDLE may be retrieved from the inode internal OSM handle storage;  
and
2. SIZE may be retrieved from the inode variable i\_size.

Each file within VFS 606 may have at least one super block, which may contain enough  
5 information about the file system to initiate activity of the file system. This super block  
is detailed in the C structure struct super\_block, such as the one described previously.

The methods variable, f\_op, may provide access to file operations. The struct  
super\_operations \*s\_op function may provide access to the root inode, which may be  
desired for the OSM.

```

10 struct file {
    struct list_head f_lst;
    struct dentry *f_dentry;
    struct file_operations *f_op;
15 atomic_t f_count;
    unsigned int f_flags;
    mode_t f_mode;
    loff_t f_pos;
    unsigned long f_reada;
20 unsigned long f_ramax;
    unsigned long f_raend;
    unsigned long f_ralen;
    unsigned long f_rawin;
    struct fown_struct f_owner;
25 unsigned int f_uid;
    unsigned int f_gid;
    int f_error;
    unsigned long f_version;
    }.
30

```

System 600 may provide one or more file operations described below. The variable f-  
>s\_op may contain the following C functions and may provide access to the super block.

```

struct file_operations {
    loff_t (*llseek) (struct file *, off_t, int)
35 ssize_t (*read) (struct file *, char *, size_t, loff_t *);

```

System 600 may provide the function **llseek** (**struct file \***, **off\_t**, **int**). This function may accept the inputs as set forth in Table 8.

# 2025 RELEASE UNDER E.O. 14176

Variable Type	Variable Identifier	Description
struct file *	File	This input may specify the file pointer to seek.
off_t	Offset	This input may specify the offset from Origin to seek to.
Int	Origin	This input may specify the Origin.

This function may send a **StreamConeSeek** message to the ISM. The message may be configured as follows:

1. HANDLE may be set from node internal storage for OSM handles; and
2. NEWPOSITION may be set to the position obtained by calculation from Offset and Origin.

System 600 may provide the function **read (struct file \*, char \*, size\_t, loff\_t)**.

This function may accept the inputs set forth in Table 9.

TABLE 9





TABLE 11

Variable Type	Variable Identifier	Description
struct file *	File	This input may specify the file pointer to read.

5 This function may send a **StreamConeEnumerate** message to the ISM. The message may be configured as follows:

1. HANDLE may be set from node internal storage for OSM handles;
2. ENUMERATOR is set to Count;
3. SGL may be set to Entry's file name buffer;
- 10 4. SGL's size may be set to 255.

System 600 may also provide a dentry interface as follows:

```

struct dentry {
    int d_count;
    unsigned int d_flags;
    15 struct inode * d_inode;
    struct dentry *d_parent;
    struct dentry *d_mounts;
    struct dentry *d_covers;
    struct list_head d_ash;
    20 struct list_head d_lru;
    struct list_head d_child;
    struct list_head d_subdirs;
    struct list_head d_alias;
    struct qstr d_name;
    25 unsigned long d_time;
    struct dentry_operations *d_op;
    struct super_block *d_sb;
    unsigned long d_reftime;
    void *d_fsdata;
    30 unsigned char d_iname[DNAME_INLINE_LEN];
}.

```

Stream tree ISM 618 may support one or more stream tree class messages, as defined herein. Stream tree 618 may function and support messages from a stream tree

OSM, such as stream tree OSM 608. Stream forest ISM 616 may support stream forest class messages, as defined herein. Stream forest ISM 616 may function and support messages from a stream forest OSM, such as stream forest OSM 602.

Stream forest ISM 616 may include a user interface. The user interface may include a user screen that may display one or more stream trees on initialization. A user may be able to create new stream trees. When creating new stream trees, the user may be presented with a screen asking for size and identification. If a stream tree is created, a stream tree class object may be created. The user may also be able to erase stream trees. The user interface may provide for confirmation of erasure of stream trees. Stream forest messages may be handled and tree objects created as appropriate.

System 600 may provide the message **StreamConeCreate**. This message may be used to create a new stream cone that will store information, and may accept the inputs as set forth in Table 12.

**TABLE 12**

Variable Type	Variable Identifier	Description
U32	HANDLE	This input may specify the handle that should be closed.
U32	TYPE	This input may specify the type to create. 1 indicates a file and 2 indicates a directory.
SGL	SGL	Specifies the identifier.

System 600 may also provide the message **StreamConeEnumerate**. This message may be used to list one or more stream cones within a stream cone container, and may accept the inputs as set forth in Table 13.

**TABLE 13**

Variable Type	Variable Identifier	Description
U32	HANDLE	This input may specify the handle that should be closed.
U32	ENUMERATOR	This input may specify a zero-based index indicating which entry should be enumerated into the SGL.
SGL	SGL	Specifies the location of the enumerated stream cone identifier.

5           System 600 may retrieve the inode relating to HANDLE from the handle manager. When an enumerator is set to 0, the “ext2fs” library call dir\_iterate() may be used with the inode relating to handle as the parent to generate a list of stream cone identifiers on the “ext2” filesystem. A list entry corresponding to the ENUMERATOR index may be copied into SGL.

10           System 600 may provide the message **StreamConeErase**. This message is used to erase a stream cone identifier, and may accept the inputs as set forth in Table 14.

**TABLE 14**

15

Variable Type	Variable Identifier	Description
U32	HANDLE	This input may specify the handle that should be closed.
SGL	SGL	This input may specify the name of the identifier that should be erased.

System 600 may provide the message **StreamConeGetInformation**. This message may be used to retrieve information about the stream cone, and may accept the inputs as set forth in Table 15.

**TABLE 15**

Variable Type	Variable Identifier	Description
U32	HANDLE	This input may specify the handle where information should be retrieved from.
SGL	SGL	This input may specify the name of the identifier that should be erased.

System 600 may provide the message **StreamConeIdentify**. This message may be used to map a handle identifier to a string identifier, and may accept the inputs as set forth in Table 16.

**TABLE 16**

Variable Type	Variable Identifier	Description
U32	PARENT HANDLE	This input may specify the parent handle stream cone container.
U32	CHILD HANDLE	This input may specify the child handle that should be mapped to the stream cone identifier.
U32	ATTRIBUTES	This input may specify the attributes of the identified stream cone.
SGL	SGL	This input may specify the name of the identifier.

System 600 may provide the message **StreamConeLock**. This message may be used to lock a byte range of a file, and may accept the inputs as set forth in Table 17.

**TABLE 17**

Variable Type	Variable Identifier	Description
U32	HANDLE	This input may specify the parent handle stream cone container.
U64	INDEX	This input may specify the byte index that should be locked.
U64	SIZE	This input may specify the size in bytes that should be locked.

System 600 may provide the message **StreamConeRead**. This message may be used to read a block from a stream cone, and may accept the inputs as set forth in Table 18.

**TABLE 18**

Variable Type	Variable Identifier	Description
U32	HANDLE	This input may specify the parent handle stream cone container.
U64	SIZE	This input may specify the size of the block to read.
SGL	SGL	This input may specify where in memory the file should be stored.

System 600 may also provide a message **StreamConeRelease**. This message may be used to close an identification of the specified handle, and may accept the inputs as set forth in Table 19.

**TABLE 19**

Variable Type	Variable Identifier	Description
U32	HANDLE	This input may specify the handle that should be closed.

This function may unlink HANDLE from the inode identifier.

System 600 may provide a message **StreamConeRename**. This message may be  
5 used to rename a stream cone, and may accept the inputs as set forth in Table 20.

**TABLE 20**

Variable Type	Variable Identifier	Description
U32	HANDLE	This input may specify the handle that should be renamed.
U32	NEWPARENT	This input may specify the current or new parent handle.
SGL	SGL	This input may specify the name of the new SGL.

10 System 600 may also provide a message **StreamConeResize**. This message is used to resize a stream cone, and may accept the inputs as set forth in Table 21.

**TABLE 21**

Variable Type	Variable Identifier	Description
U32	HANDLE	This input may specify the handle that should be renamed.
U64	SIZE	This input may specify the new size of the stream cone.

System 600 may provide a message **StreamConeSeek**. This message is used to change the position of a stream cone, and may accept the inputs as set forth in Table 22.

**TABLE 22**

Variable Type	Variable Identifier	Description
U32	HANDLE	This input may specify the handle that should be renamed.
U64	NEW POSITION	This input may specify the new position of the stream cone.

System 600 may provide a message **StreamConeSetInformation**. This message may be used to set information regarding the stream cone, and may accept the inputs as set forth in Table 23.

**TABLE 23**

Variable Type	Variable Identifier	Description
U32	HANDLE	This input may specify the handle that should have information set.
SGL	SGL	This input may specify the information set block.

System 600 may provide a message **StreamConeUnlock**. This message may be used to unlock a previously set byte lock range, and may accept the inputs as set forth in Table 24.

**TABLE 24**

Variable Type	Variable Identifier	Description
U32	HANDLE	This input may specify the handle that should be unlocked.
U64	INDEX	This input may specify the start byte of the range of bytes to unlock.
U64	BYTECOUNT	This input may specify the byte count to unlock.

System 600 may provide a message **StreamConeWrite**. This message may be used to write a block to a stream cone, and may accept the inputs as set forth in Table 25.

**TABLE 25**

Variable Type	Variable Identifier	Description
U32	HANDLE	This input may specify the handle that should be written.
U64	BYTECOUNT	This input may specify the count in bytes that should be written.
SGL	SGL	This input may specify the block to be written.

While certain features of the embodiments of the invention have been illustrated as described herein, many modifications, substitutions, changes and equivalents will now occur to those skilled in the art. It is, therefore, to be understood that the appended claims are intended to cover all such modifications and changes as fall within the true spirit of the embodiments of the invention.